



兰州大学  
LANZHOU UNIVERSITY

# FLUKA combinatorial geometry

23rd FLUKA Beginner's Course  
Lanzhou University  
Lanzhou, China  
June 2–7, 2024



- the **Geometry** is the description of the part of space where particles should be transported
- In real world, the geometry it is made of **objects**, occupying **positions**
  - a **detector** at **1m** from a **target**
- In FLUKA, objects are called **Regions**
- Each region is identified by a number and a name<sup>1</sup>
- Like objects, each region must have a **material** assigned to it
- Other simulation parameters can be assigned "**by region**", for instance electron transport thresholds.
- Positions are defined in a cartesian system with distances in units of **cm**
- Regions are constructed from building blocks called **Bodies**
- through **Boolean** operations


<sup>1</sup>In old versions, only the number



Basic objects called **bodies** (such as cylinders, spheres, parallelepipeds, etc.) are combined to form more complex objects called **regions**

This combination is done using Boolean operations




Math	Operation	FLUKA	Meaning (A and B bodies)
$\cup$	Union	$A \mid B$	All what is in A <b>and</b> all what is in B
$\cap$	Intersection	$A + B$	What is in <b>both</b> A and B
$-$	Subtraction	$A - B$	What is in A <b>and not</b> in B





**Zones:** sub-regions defined only via bodies intersection and subtraction

- The Fluka transport works with **Zones**, because they ensure that a trajectory can have only one entrance and one exit point. Would not be true for Unions, that can even be disjointed
- A region can, instead, be the Union of many zones
- Moreover, the use of Zones adds flexibility to the construction of regions





- The geometry must be contained within an outer border
- And surrounded by a region made by **Blackhole** : an all-absorbing material
- Every point within the geometry must belong to one region
  - Not only objects, but also space in between objects must be assigned to one (or more) regions.
  - No holes can be left.
- Every point within the geometry must belong to only one region:
  - region overlaps are not allowed
- However, Zones belonging to the same region can overlap.



CG input must respect the following structure:

**GEOBEGIN** card

name of geometry input file, optional, see later

name of geometry log file, optional, see later

**VOXELS** card (optional, see medical lecture)

Geometry title and options line (formatted, see later)

**Body data**

**END** card

**Region data**

**END** card

**LATTICE** card (optional, for repeated structures)

Region volumes (optional, see later)

**GEOEND** card

An asterisk (\*) in the 1st column comments the line

No blank line are allowed No tabs are allowed



The input file format for the geometry is different from the one adopted anywhere else in FLUKA (i.e. the number and length of the input fields is different)

Different formats can be used (due to backward compatibility)

- **Fixed Format** (old format, not used nor described in this lecture)
  - Alignment is mandatory
  - Bodies and regions are identified by numbers (rather than names)
- **Name based Format (recommended)**
  - no alignment
  - Bodies and regions are identified by **names**
  - parentheses can be used to perform complex Boolean operations (advanced)
  - **It is not the default**, it is activated through the **GLOBAL** or **GEOBEGIN** card

**Internally** regions are identified by **numbers**

- In some of the output/error messages numbers are used
- Numbers and Names are printed in the .out file
- Name  $\leftrightarrow$  Number functions are available for user routine coding (advanced)



- WHAT(1) >0 switches on online parenthesis expansion (see FLUKA manual)
- WHAT(2) set accuracy parameter – use only if necessary ! See later
- WHAT(3) logical unit for the geometry input. Default is from input file  
Geometry input **can be read from a separate file**. If set should be >20.0
- WHAT(4) logical unit for the geometry output; Default is standard output  
Where the “interpreted” geometry echo is written. If set should be >20.0
- WHAT(5) Parenthesis optimization level (see FLUKA manual)
- WHAT(6) if >0 debugging printout (dangerous!! can be huge!)
  - SDUM **COMBNAME** or COMBINAT  
COMBNAME selects name based format, COMBINAT fixed format  
Default: COMBINAT (!)  
Is overwritten by WHAT(5) of a possible **GLOBAL** card



This card has no keyword, it must follow the **GEOBEGIN** card (unless voxels are used) and its format is **(2I5, 10X, A60)**

The card gets three inputs: **IVLFLG, IDBG, TITLE**

**IVLFLG** (Input VoLumes FLAG) enables the normalization of the quantities scored in regions by the option **SCORE**

**IVLFLG= 0** → no normalization applied (default)

**IVLFLG= 3** → results divided by region volumes to be input by the user before **GEOEND**. See manual, seldom used.

**IDBG** selects different kinds of geometry fixed format input: ( not used in COMBNAME)  
**IDBG = 0** : default fixed format  
**IDBG = -10 or -100** : high accuracy fixed format

**TITLE** Custom, optional. Must start after column 20

Flair merges this line with the **GEOBEGIN** card

The screenshot shows a graphical user interface for editing input cards. The top bar is yellow and contains the following controls: **GEOBEGIN** (in red), Log: ▾, Geometry: ▾, Acc: ▾, Out: ▾, Opt: ▾, and Fmt: COMBNAME ▾. Below this, the text "Title: my first geometry" is entered. A scrollable area below shows the resulting merged card: **GEOBEGIN** followed by a table with columns 1 through 7. The first two columns contain the number 0, the third column contains the text "my first geometry", and the seventh column contains "COMBNAME".




The geometry input can be prepared in a file separated from the input file  
Useful in case of shared geometries and/or common to different applications

- with the `#include` preprocessor directive or
- from the `GEOBEGIN` card:
  - set `what(3)` and `what(4)` to non zero ( $21 < \text{what} < 100$ , logical units)
  - Add two lines after the `GEOBEGIN` card with  
name of the geometry file  
name of the geometry log file

```
GEOBEGIN          21  22          COMBNAME
mygeo.geo
mygeo.scr
GEOEND
```






Bodies:

- basic convex objects (like a sphere or a cube)
- plus infinite planes (half-spaces)
- infinite cylinders (circular and elliptical)
- and generic quadric surfaces (surfaces described by 2nd degree equations)

Each body divides the space into two domains: inside and outside.  
In the Fluka boolean language, inside is +, outside is -

Each body is identified by a three characters code



RPP:	Rectangular Parallelepiped
SPH:	Sphere
XYP, XZP, YZP:	Infinite half space delimited by a Plane $\perp$ to the z, y, x axis
PLA:	Generic infinite half-space, delimited by a Plane
XCC, YCC, ZCC:	Infinite Circular Cylinder, parallel to coordinate axis
XEC, YEC, ZEC:	Infinite Elliptical Cylinder, parallel to coordinate axis
RCC:	Right Circular Cylinder
REC:	Right Elliptical Cylinder
TRC:	Truncated Right angle Cone
ELL:	Ellipsoid of revolution
QUA:	Quadric
PYX, PYY, PYZ:	Pyramid parallel to a coordinate axis.
Deprecated bodies: ARB, RAW, WED, BOX : do not use!!!	




- The input for each body consists of:
  - the 3-letter code indicating the body type (RPP, ZCC...)
  - a unique "body name" (alphanumeric identifier, 8 character maximum, case sensitive)
  - a set of geometrical quantities defining the body (the number depends on the body type, see next slides)
- geometrical quantities can extend over as many lines as needed (Maximum 132 characters per line accepted)
- geometrical quantities have to be separated by **one or more blanks**, or by one of the separators `,` `/` `;` `:`
- Each body divides the space in two. Inside and Outside
- The normal vector points towards Outside

**All values are in cm!**

An RPP has its edges parallel to the coordinate axes

It is defined by 6 numbers in the following order:

$X_{min}$  ,  $X_{max}$  ,  $Y_{min}$  ,  $Y_{max}$  ,  $Z_{min}$  ,  $Z_{max}$




```
RPP      eg_RPP      Xmin:-5.0      Xmax: 5.0
          Ymin: 0.0      Ymax: 10.0
          Zmin:-30.0     Zmax: 30.0
```

---

```
*...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...
RPP eg_RPP      -5.0 5.0 0.0 10.0 -30.0 30.0
```


A SPH is defined by 4 numbers:  
**V<sub>x</sub>, V<sub>y</sub>, V<sub>z</sub>** :coordinates of the centre  
**R**: radius



SPH	eg_SPH	x:0.0	y:0.0	z:0.0
		R:10.0		

```

+...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...
SPH eg_SPH  0.0 0.0 0.0 10.0
    
```



There are 4 kinds of infinite half-spaces

Three are delimited by planes perpendicular to the coordinate axes:

- 1 Delimited by a plane  $\perp$  to the x-axis. Code: **YZP**
- 2 Delimited by a plane  $\perp$  to the y-axis. Code: **XZP**
- 3 Delimited by a plane  $\perp$  to the z-axis. Code: **XYP**

All defined by a single number:


$V_x$  (resp.  $V_y$ , or  $V_z$ ),

coordinate of the plane on the corresponding axis.


Points for which:  $x < V_x$  (resp.  $y < V_y$ , or  $z < V_z$ )

are **inside the body**

**XYP** MyXYP 10.0



A PLA defines the infinite half space delimited by a generic plane



A PLA is defined by 6 numbers:

**Hx, Hy, Hz** :vector  $\perp$  to the plane, arbitrary length;

**Vx, Vy, Vz** :any point lying on the plane

The half-space **inside the body** is that from which the vector is pointing (i.e. **the normal points outside**).

```
PLA eg_PLA Nx: 0.0 Ny: 1.0 Nz: 1.0
          x: 1. y: 2. z: 3.
+...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...
PLA eg_PLA 0.0 1.0 1.0 1. 2. 3.
```


An RCC can have any orientation in space  
It is limited by a cylindrical surface and two plane faces  $\perp$  to its axis.

Each RCC is defined by 7 numbers:

**V<sub>x</sub>, V<sub>y</sub>, V<sub>z</sub>** : centre of one face

**H<sub>x</sub>, H<sub>y</sub>, H<sub>z</sub>** : vector corresponding to the cylinder height, pointing toward the other face

**R** : cylinder radius.



```
RCC      eg_RCC      x: 0.0      y: 0.0      z: 0.0
              Hx: 0.0      Hy: 10.0     Hz: 10.0
              R: 2.0
```

---

```
*...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...
RCC eg_RCC  0.0 0.0 0.0 0.0 10.0 10.0 2.0
```




Each XCC ( YCC, ZCC) is defined by 3 numbers

**A<sub>y</sub>, A<sub>z</sub>** for XCC

(**A<sub>z</sub>, A<sub>x</sub>** for YCC, **A<sub>x</sub>, A<sub>y</sub>** for ZCC) :coordinates of the cylinder axis

**R** : cylinder radius.



ZCC	eg_ZCC	x:0.0	y:0.0	R:20.0
*...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...				
ZCC eg_ZCC	0.0 0.0 20.0			



Are less frequently used, their description is in the manual



## Reminder:

Regions are composed by one or more **Zones**

Joined together by **Union** sign: (|)

A Zone is obtained by Intersection(+) or Subtraction (-) of bodies

Regions but must be of homogeneous material composition.

Each point of space must belong to **one and only one** region!



Input for each region starts on a new line and extends on as many continuation lines as are needed. It is of the form:

REGNAME NAZ boolean-zone-expression

or

REGNAME NAZ boolean-zone-expression | boolean-zone-expression | ...

- REGNAME is the region name
  - alphanumeric identifier,
  - 8 character maximum,
  - case sensitive.
  - Must start by an alphabetical character
- NAZ See next slide
- boolean-zone-expression See next slides



**NAZ** stands for Number of Adjacent Zones:

- When tracking, the code discovers and keeps memory of the zones a particle can enter when leaving the current one,
- So that it saves time by checking first the zones in this “neighbor list” , before scanning the others.
- this list has a global dimension for the whole set of regions, cannot be  $\infty$
- Dimension is calculated at initialization as sum of the **NAZ**s for all the regions
- When the the list is full the code prints a warning: GEOMETRY SEARCH ARRAY FULL. This is not lethal: the calculation continues but with a reduced efficiency

## NAZ


**NAZ** is a rough estimate of the number of zones a particle can enter when leaving the current region

It is only an “efficiency” parameter

If you do not know.. 5 is usually a good candidate


- a **REGION** is the union ( $\cup$ ) of one or more **ZONES**
- a **ZONE** is defined by intersections ( $+$ ) and/or subtraction ( $-$ ) of bodies
- 

```
RPP Body1 -5.0 5.0 0. 10. -30. 30.  
END
```



- a **REGION** is the union ( $\cup$ ) of one or more **ZONES**
- a **ZONE** is defined by intersections (+) and/or subtraction (-) of bodies
  - **+body**: only the inner part of the body can belong to the zone (means that the zone being described is fully contained inside this body)

```
RPP   Body1  -5.0  5.0  0.  10.  -30.  30.  
END  
InRPP 5  +Body1  a single-zone region
```




- a **REGION** is the union (|) of one or more **ZONES**
- a **ZONE** is defined by intersections (+) and/or subtraction (-) of bodies
  - **+body**: only the inner part of the body can belong to the zone (means that the zone being described is fully contained inside this body)
  - **-body** only the outside of the body can belong to the zone (means that the zone being described is fully outside this body)

```
RPP Body1 -5.0 5.0 0. 10. -30. 30.
```

```
END
```

```
InRPP 5 +Body1 a single-zone region
```

```
OuRPP 5 -Body1 is this ok?
```



- a **REGION** is the union ( $\cup$ ) of one or more **ZONES**
- a **ZONE** is defined by intersections (+) and/or subtraction (-) of bodies
  - **+body**: only the inner part of the body can belong to the zone (means that the zone being described is fully contained inside this body)
  - **-body** only the outside of the body can belong to the zone (means that the zone being described is fully outside this body)
  - Zones must be **finite**: there must always be at least a + sign. (otherwise the tracking would never end...)


```
RPP Body1 -5.0 5.0 0. 10. -30. 30.
```

```
END
```

```
InRPP 5 +Body1 a single-zone region
```

```
OuRPP 5 -Body1 is this ok?
```


```
OuRPP 5 -Body1 no, missing +:
```





- a **REGION** is the union (|) of one or more **ZONES**
- a **ZONE** is defined by intersections (+) and/or subtraction (-) of bodies
  - **+body**: only the inner part of the body can belong to the zone (means that the zone being described is fully contained inside this body)
  - **-body** only the outside of the body can belong to the zone (means that the zone being described is fully outside this body)

```

RPP   Body1  -5.0  5.0    0.  10.  -30.  30.
SPH   Outside  0.   0.   1000.
END
InRPP 5                +Body1  a single-zone region
OuRPP 5  -Body1 +Outside
    
```



playing with three RPP's





$$\text{Zone1} = +\text{Body1} + \text{Body3}$$

(Zone1 is the space common to Body1 and Body3)

$$\text{Zone2} = +\text{Body2} - \text{Body1}$$


(Zone2 is the space inside of Body2 but outside of Body1)

playing with three RPP's define the red and the white region



RedF	5	+Body1 +Body3	+Body2 -Body1
WhiteF	5	+Body3 -Body1	+Body1 -Body3

playing with three RPP's All as a single region



```
ALLF 5 | +Body1 | +Body2 | +Body3
```

Zones of the same region can overlap



In name based format one can also use parentheses to form more complex Boolean operations

Advanced topic, Not described in this course



All particles entering a black-hole are absorbed (they vanish)

FLUKA geometry **MUST** be embedded into a **BLCKHOLE** region  
to avoid tracking particles to infinity

The outer surface of the BLCKHOLE region must be closed.

Further black-hole regions can be defined by the user if desired


**BLCKHOLE** region: has material **BLCKHOLE** assigned to it

How to define the Black Hole? Remember, it must be a REGION, not a body  
Usually as the region contained between two large spheres, enclosing your geometry and a bit more

All the space points at the interior of the Black Hole must belong to some region

For really empty space, one can assign material **VACUUM** to it


```
SPH   Black   0.0  0.0   0.  10000.
SPH   Void    0.0  0.0   0.0  1000.
RPP   Body1   -5.0  5.0   0.   100.   -5.0  5.0
RPP   Body2   -5.0  5.0  70.0  80.0   -5.0  30.
RPP   Body3   -5.0  5.0  90.0  100.0  -5.0  30.
END
BLKH  5                +Black -Void
VOID  5  +Void -Body1 -Body2 -Body3
ALLF  5  | +Body1 | +Body2 | +Body3
END
```



```


TITLE
f
DEFAULTS
GEOBEGIN
  0 0          A solid F letter
SPH  Black  0.0  0.0  0.  10000.
SPH  Void   0.0  0.0  0.0  1000.
RPP  Body1  -5.0  5.0  0.   80.  -5.0  5.0
RPP  Body2  -5.0  5.0  50.0 60.0  -5.0  30.
RPP  Body3  -5.0  5.0  70.0 80.0  -5.0  30.
END
BLKH 5  +Black -Void
VOID 5  +Void  -Body1 -Body2 -Body3
ALLF 5  | +Body1 | +Body2 | +Body3
END
GEOEND
ASSIGNMAT BLCKHOLE  BLKH
ASSIGNMAT VACUUM    VOID
ASSIGNMAT COPPER    ALLF
  
```

PRECISIO  
COMBNAME




“Infinite” bodies, planes and cylinders, are really useful and allow for fast tracking. They are strongly recommended. Here a simple exemple of use.

Imagine you want to model an hemispherical cup




“Infinite” bodies, planes and cylinders, are really useful and allow for fast tracking. They are strongly recommended. Here a simple exemple of use.

Imagine you want to model an hemispherical cup  
That is, one half of the space in between two spheres.



“Infinite” bodies, planes and cylinders, are really useful and allow for fast tracking. They are strongly recommended. Here a simple exemple of use.


Imagine you want to model an hemispherical cup  
That is, one half of the space in between two spheres.  
So, we take the space between two spheres





“Infinite” bodies, planes and cylinders, are really useful and allow for fast tracking. They are strongly recommended. Here a simple exemple of use.

Imagine you want to model an hemispherical cup  
That is, one half of the space in between two spheres.  
So, we take the space between two spheres  
and we “cut” in the middle.  
With? A plane.



# Example with a plane

## Writing the geo



The black hole must be there

```
SPH      Black  0.0  0.0  0.  10000.  
SPH      Void   0.0  0.0  0.0  1000.  
  END  
BLKH     5  +Black -Void  
  END
```

# Example with a plane

## Writing the geo




Add two spheres

```
SPH      Black  0.0  0.0  0.  10000.
SPH      Void   0.0  0.0  0.0  1000.
SPH      OutSph 0.   0.   0.   100.  sphere at origin, R=100 cm
SPH      InSph  0.   0.   0.   80.   sphere at origin, R=80 cm
END
BLKH     5  +Black -Void
END
```


# Example with a plane

## Writing the geo



And build a region with the space between spheres. Do not forget the space around!  
And fill it with something to drink

```
SPH      Black  0.0  0.0  0.  10000.
SPH      Void   0.0  0.0  0.0  1000.
SPH      OutSph 0.    0.    0.   100.  sphere at origin, R=100 cm
SPH      InSph  0.    0.    0.    80.   sphere at origin, R=80 cm
END
BLKH     5  +Black -Void
CUP      5  +OutSph -InSph
VOID     5  +Void -OutSph
MILK     5  +InSph
END
```



# Example with a plane


## Writing the geo



Add a plane to cut in two parts

```
SPH      Black  0.0  0.0  0.  10000.
SPH      Void   0.0  0.0  0.0  1000.
SPH      OutSph 0.   0.   0.   100.  sphere at origin, R=100 cm
SPH      InSph  0.   0.   0.   80.   sphere at origin, R=80 cm
XZP      Zero   0.
END
BLKH     5  +Black -Void
CUP      5  +OutSph -InSph
VOID     5  +Void -OutSph
MILK     5  +InSph
END
```

Plane  $\perp$  y, at y=0



# Example with a plane

## Writing the geo




cut the region

```
SPH   Black  0.0  0.0  0.  10000.
SPH   Void   0.0  0.0  0.0  1000.
SPH   OutSph 0.  0.  0.  100.
SPH   InSph  0.  0.  0.  80.
XZP   Zero   0.
END
BLKH  5  +Black -Void
      CUP  5  +OutSph -InSph +Zero
      END
```

sphere at origin, R=100 cm

sphere at origin, R=80 cm

Plane  $\perp$  y, at y=0



# Example with a plane


## Writing the geo



take care of surroundings and content

```
SPH      Black  0.0  0.0  0.  10000.
SPH      Void   0.0  0.0  0.0  1000.
SPH      OutSph 0.    0.    0.    100.  sphere at origin, R=100 cm
SPH      InSph  0.    0.    0.    80.   sphere at origin, R=80 cm
XZP      Zero   0.
END
BLKH     5  +Black -Void
  CUP     5  +OutSph -InSph +Zero
VOID     5  | +Void -Zero | +Void +Zero -OutSph
END
```

Plane  $\perp$  y, at y=0




# Example with a plane

## Writing the geo



take care of surroundings and content

```
SPH      Black  0.0  0.0  0.  10000.
SPH      Void   0.0  0.0  0.0  1000.
SPH      OutSph 0.   0.   0.   100.  sphere at origin, R=100 cm
SPH      InSph  0.   0.   0.   80.   sphere at origin, R=80 cm
XZP      Zero   0.                                     Plane  $\perp$  y, at y=0
END
BLKH     5    +Black -Void
  CUP     5    +OutSph -InSph +Zero
VOID     5    | +Void -Zero | +Void +Zero -OutSph
MILK     5    +InSph +Zero
END
```





Whenever it is possible, the following bodies should be preferred:

PLA, RPP, SPH, XCC, XEC, XYP, XZP, YCC, YEC, YZP, ZCC, ZEC, QUA

These bodies make the tracking faster thanks to special extra coding

## Precision

Always use as many digits as possible in the definition of the body parameters, particularly for body heights (RCC, REC, TRC), and for direction cosines of bodies with slant surfaces.




- FLUKA uses systematically double precision mathematic (i.e. 16 significant digits)
- The relative accuracy (RA) achievable in double precision is of the order of  $10^{-14}$ - $10^{-15}$
- A particle can never be **exactly** on a boundary : can be within a given precision
- FLUKA uses by default  $10^{-10}$  cm as absolute accuracy (AA) during tracking
- This has to be compared with the geometry size:
  - Ex: atmospheric showers: at the earth radius,  $R \approx 6 \cdot 10^8$  cm, the rounding is of the order of  $10^{-14} \times 6^8$  cm =  $10^{-6}$  cm. The condition " I am on a boundary if the distance is  $< 10^{-10}$  cm" has a random outcome and makes the tracking crazy
  - Conversely, for really small geometries, one could wish better accuracy
- **GEOBEGIN's** WHAT(2) can be used to change the AA:  $AA = \text{WHAT}(2) \cdot 10^{-6}$  cm
- AA should be larger than  $RA \cdot L$  , being L the largest **coordinate value** in the considered problem, (except black hole)
- **The default** ( $\text{WHAT}(2) = 10^{-4}$ ) is **OK for most** geometries ( $L < 100$  m)




Imagine to have two cylindrical regions next to each other. The most natural solution would be to use two adjacent RCC (cylinders delimited by faces)

Imagine to have two cylindrical regions next to each other. The most natural solution would be to use two adjacent RCC (cylinders delimited by faces)




Imagine to have two cylindrical regions next to each other. The most natural solution would be to use two adjacent RCC (cylinders delimited by faces)




this means that the **same surface** is defined in **two different** ways, in A and in B. Rounding may be different, especially for complex surfaces and/or non-optimized AA

Imagine to have two cylindrical regions next to each other. The most natural solution would be to use two adjacent RCC (cylinders delimited by faces)



Rounding may be different on A and B, resulting in tracking errors


Imagine to have two cylindrical regions next to each other. The most natural solution would be to use two adjacent RCC (cylinders delimited by faces)



Rounding may be different on A and B, resulting in tracking errors

If possible, avoid touching surfaces

- Use a single RCC cut in two parts by a plane
- Or force partial overlap of RCCs





During execution the code needs to know the region where a particle is located at every step

- The program will stop if a particle position does not belong to any region
- An error message will be printed in the `.err` file with the particle position and direction
  - The problem might be at the present position (E.g. rounding on a boundary)
  - Or far away: next region not found
- **IMPORTANT!** Tracking will not stop if a particle position belongs to more than one region. It will accept the first region it finds but the results will be completely unreliable!!
- **WARNING** `flair` will **NOT** detect and signal geometry errors if they are not contained in at least one of the views: always inspect the whole geometry



- Problem space not enclosed by a black body region
- Never start a primary particle along a surface. You could get a geometry error even if the geometry is correct because FLUKA cannot determine the starting region
- Precision errors: always give as many digits as possible
- Lattice replica  $\leftrightarrow$  basic cell mismatch (Lattices not covered in this course)



- **GEOEND** card with the **DEBUG** SDUM
- Error messages during simulation in the .err file
- Geometry plot by Flair (it automatically invokes the **PLOTGEOM** card)
- FLAIR geoviewer
  - extremely powerful, it saves you!. However:
  - Be sure to cover the whole geometry
  - flair-geoviewer uses a mathematical representation different from the one in fluka. Rarely, inconsistencies show up. Should it happen, please report to the developers.

**GEOEND** card can activate the geometry debugger.

For every node of a cartesian mesh selected by the user, it checks whether the point is assigned to one and only one region.


Two cards are needed

<b>GEOEND</b>	Xmax	Ymax	Zmax	Xmin	Ymin	Zmin	<b>DEBUG</b>
<b>GEOEND</b>	Nx	Ny	Nz				<b>&amp;</b>

In flair, add the **GEOEND** card



click on the small arrow to activate the DEBUG fields





- If no error is found, no .err file will be created
- If the debugger does not find any error it does not mean that the geometry is error free!
- One has to test, changing the GEOEND settings especially for critical and complicated regions
- If too many errors are found, the program stops
- Errors will be listed in the .err file in the form:

```
**** Lookdb: Geometry error found ****  
**** The point: -637.623762 -244.554455 -96.039604 ****
```

Overlap of regions:

```
**** is contained in more than 1 region ****  
**** (regions: 6 7) ****
```

Undefined space:

```
**** is not contained in any region
```



The FLUKA geometry has more capabilities, not covered in this course. You can explore them through the manual, or by looking at the Geometry lecture in the last advanced course <https://agenda.infn.it/event/20624/timetable/>

Briefly

- **Parentheses** group boolean operations like in algebra
- **Translation, Rotation, Expansion** of bodies. For example, `$Start_translat.....$End_translat` allow to move one or more bodies by given amounts along the three axis
- **ROT-DEFI** card defines rototranslation, to be used on bodies, lattices, binnings
- **LATTICE** card defines replicas of parts of the geometry
- **VOXELS** Defines a part of the geometry as composed by voxels (see lecture on medical applications )



### Body

Basic objects to build the geometry: bodies

Each body divides the space into **Inside** and **outside**


### Zone

a Zone is a part of space defined as **intersection (+)** and/or **subtraction (-)** of bodies  
can be interpreted as a sub-region

### Region

a Region is the **union (|)** of one or more Zones.

This is the real “object”, it will have materials and properties assigned to it



### Names

Both bodies and regions are identified by **names** chosen by the user  
name = alphanumeric identifier, 8 character maximum, case sensitive

### Black Hole

The geometry must be enclosed in a region filled with BLCKHOLE  
Particles entering in a BLCKHOLE region are immediately killed

### completeness and unicity

Every point of the space enclosed by the black hole must belong to **one and only one** region



Questions?

Next: geometry exercise

Have fun!